

## IN THE CLAIMS

1-10. (canceled)

11. (new)      A holster for a firearm, comprising: a case, wherein said case comprises

a)      a base, said base equipped with guides for a slide, and wherein said case has in its cross section a form of an arch with formation of a groove along said case for a grip of said firearm,;

b)      a front cut of a barrel of said firearm comprising a hole for said barrel; and

c)      a means to switch a safety lock over, said means made on the lateral wall at the side of the safety lock in the form of a figured window in the shape of a one sided trapezium.

12. (new)      The holster of claim 1, wherein a central part of said case further comprises a window made to throw away a cartridge.

13. (new)      The holster of claim 2, wherein said window is located on the lateral side in the area of a location of the window on the pistol to throw away a cartridge cases.

14. (new)      The holster of claim 1, wherein said holster further comprises an element to fix said holster to a user.

15. (new)      A holster for a firearm, comprising: a case, wherein said case comprises

a) a base, wherein said base comprises guides for a slide, and wherein said base has in its cross section a form of an arch with formation of a groove along the case for a grip of said firearm;

b)      a spring-loaded latch made in the form of a plate, said latch configured for turning along the direction of the movement of the pistol;

c)      a means to switch over a safety lock in the form of a figured window in the shape of a one-sided trapezium; and

d) a supporting lug for the frame of the pistol, wherein the length of said supporting lug exceeds the maximum size of the figured window.

16. (new) The holster of claim 5, wherein corners of said figured window are round.

17. (new) The holster of claim 5, wherein corners of said lug are made round.

18. (new) The holster of claim 5, wherein a central part of said case further comprises a window made to throw away a cartridge.

19. (new) The holster of claim 8, wherein said window is located on the lateral side in the area of a location of the window on the pistol to throw away a cartridge cases.

20. (new) The holster of claim 5, wherein said holster further comprises an element to fix said holster to a user.

21. (new) A method of getting a firearm ready for firing using one hand, comprising:  
a) providing a holster, wherein said holster comprises a case, said case comprising:

i) a base, said base equipped with guides for a slide, and wherein said case has in its cross section a form of an arch with formation of a groove along said case for a grip of said firearm,;

ii) a front cut of a barrel of said firearm comprising a hole for said barrel; and

iii) a means to switch a safety lock over, said means made on the lateral wall at the side of the safety lock in the form of a figured window in the shape of a one sided trapezium.

b) shifting the barrel of said firearm about said slide in said holster, until the cartridge chamber is completely open and the cartridge is sent into it, wherein switching over the safety lock and shifting the barrel are carried out by rectilinear pushing through the pistol with one hand in said holster.